



LOW ODOUR



LONG LASTING COLOUR



EASYCLEAN

PRODUCT INFORMATION

DESCRIPTION	Dulux Professional Interior Anti-bacteria is a high-quality interior paint specially formulated for masonry surfaces esp. ceilings. It provides: Anti-bacteria properties, fungus and mould resistance, long lasting colour and low VOC & low odour.
BENEFITS	<ul style="list-style-type: none"> • Anti-bacteria properties • Fungus and mould resistance • Long lasting colour • Low odour
USAGE	Ideal for new and previously painted interior masonry, plaster, and building boards surfaces.
PACK SIZE	18 litres
COLOUR RANGE	More than 1.000 colours, refer to Colour Pallet.

PHYSICAL FILM PROPERTIES

Water Resistance	Resistant to the levels of atmospheric humidity normally experienced in exterior environments.
-------------------------	--

PRODUCT DATA

Composition	Polymer-based emulsion & powders (46 – 68%), additives (1 – 10%) & water (31 – 44%)
Drying Time	Single wet coat at standard thickness 100 micron:
Touch Dry	30 minutes
Recoat	1 - 2 hours
Theoretical Coverage	The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity 12-14 m ² /litre/coat..
Finishing	Matt



CERTIFICATE


Singapore Green Building



Certified Vietnamese technical regulations: QCVN 16:2014/BXD

APPLICATION GUIDE
Surface Preparation

- Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax.
- Remove all loose or defective paint or powdery residues by thorough brushing and scraping, using a stiff fiber brush and high pressure water jet.
- Treat any areas affected mould, lichens, algae and moss with fungicidal treatment
- Repair any surface defects with an appropriate filler.
- Surfaces that remain powdery, friable or chalky after thorough preparation should be sealed with one coat of an appropriate Primer (see below System Recommendation).
- Do not paint if the wall is saturated with dampness. (Protimeter reading higher than 16%). Allow excess moisture to evaporate.

Note: Do not apply Dulux Professional Interior Anti-bacteria during wet weather or if the weather temperature is below 10°C.

Application Tools

By roller, brush or conventional /airless spray

Dilution

Ready to use. Dilute up to 10% with potable water when necessary if application by brush or roller. For conventional spray application, thin up to 30%.

Note: Excessive dilution from that recommended will result in low coverage and may impact application properties and color.

PAINT	SKIM COAT	Sealer (1 coat)	Topcoat (2 coats)
New wall surface	Dulux Professional Interior Putty A500	Dulux Professional Interior Sealer A500	Dulux Professional Interior Antibacteria
Old wall surface	N/A		

For alternative coating systems, please refer to our Sales Representative

Cleaning Up

Clean all equipment with clean water immediately after use.

HEALTH, SAFETY & ENVIRONMENT INFORMATION

Please refer to Product Safety Data Sheet